


CODE 1254/1255/1256



- Crochet cintré à chaud sans soudure
- Matière : acier allié haute résistance classe 8
- Seamless hot-forged hook
- Material : high strength alloy steel grade 80
- Warmgebogener Haken, ohne Schweißnähte
- Werkstoff: hochfeste Stahllegierung, GK 8

Hooks J2

WLL kg	A mm	B mm	C mm	D mm	E mm	R1 mm	Weight kg	REF
100	8	72	16	16	12	8	0,1	1254A
150	10	90	20	20	15	10	0,1	1254B
200	12	108	24	24	18	12	0,2	1254C
300	14	126	28	28	21	14	0,4	1254D
400	16	144	32	32	24	16	0,5	1254E
500	18	162	36	36	27	18	0,8	1254F
600	20	180	40	40	30	20	1,0	1254G

Hooks J3

WLL kg	A mm	B mm	C mm	D mm	E mm	R1 mm	Weight kg	REF
80	8	104	24	20	16	12	0,1	1255A
120	10	130	30	25	20	15	0,2	1255B
170	12	156	36	30	24	18	0,3	1255C
250	14	182	42	35	28	21	0,5	1255D
300	16	208	48	40	32	24	0,7	1255E
400	18	234	54	45	36	27	1,0	1255F
500	20	260	60	50	40	30	1,4	1255G

Hooks J4

WLL kg	A mm	B mm	C mm	D mm	E mm	R1 mm	Weight kg	REF
70	8	128	32	24	16	16	0,1	1256A
100	10	160	40	30	20	20	0,2	1256B
150	12	192	48	36	24	24	0,4	1256C
200	14	224	56	42	28	28	0,6	1256D
250	16	256	64	48	32	32	0,9	1256E
300	18	288	72	54	36	36	1,2	1256F
400	20	320	80	60	40	40	1,7	1256G

Disponible en stock / Available in stock / Auf Lager verfügbar

Nous consulter pour toute réalisation spécifique / Please contact us for customised product inquiry / Kontaktieren Sie uns für alle Spezialanfertigungen

www.lifteurop.com ■ E-mail : info@lifteurop.com

25, Salzbaach ■ L-9559 Wiltz ■ Tél. : +352 26 95 19-1